

# Precision Plumbing Products "Specify with Confidence - Install with Pride"



### **NICKEL PLATED FLUID HAMMER ARRESTORS**



#### **Water Hammer Arrestors (Nickel Plated)**

Normal operating pressure 35 to 250 PSIG. Spike pressure not to exceed 400 PSIG.

#### **Arrestor Construction:**

#### **Threaded Adapter:**

Machined of C69300 ECO Lead Free Brass.

Type L copper barrel, Polycarbonate Dow Calibre 2016 MFR piston, Nitrile "O" rings, Brass or Copper Cap depending on size. All parts 100% Nickel Plated.

#### **Application:**

Sea water, Petroleum, Chemicals and Corrosive fluids. Available in NPT or BSP threads.

Manufacturing lead time: 4-6 weeks.

PART NO.	SIZE
SNP-500	1/2"
SNP-750	3/4"
SNP-1000	1"
SNP-1250	1"
SNP-1500	1"
SNP-2000	1"

No access panel required.

Consult Local Code.

#### **PROJECT SUBMITTAL**

Project:
•
Contractor:
Engineer:
Date Submitted:
Prepared By:

# Over 40 years of outstanding performance

## **Precision Plumbing Products**

Division of JL Industries, Inc.

802 SE 199th Avenue Portland, Oregon 97233 T (503) 256-4010





