




ARMFLEX

Rubber Expansion Joint

Item No. **AMU**
 Name **TWIN-SPHERE CONNECTION**
 With Union Thread

SYMBOL	PART	ENGINEERING MATERIAL
1	UNION	FB32
2	REINFORCING CLOTH	NYLON FABRIC
3	ELASOMER	SYNTHETIC RUBBER

STANDARD ITEM EMPLOYS BS UNION, MAYBE REPLACED WITH ANSI, DIN AND OTHER STANDARD.




Dimension (mm)


Item	L	Allowable Movements			
		Axial		Transverse Movement	Angular Deflection
		Compression	Elongation		
15(1/2")	202mm	22mm	6mm	22mm	30°
20(3/4")	203	22	6	22	30°
25(1")	203	22	6	22	25°
32(1-1/4")	203	22	6	22	25°
40(1-1/2")	203	22	6	22	20°
50(2")	203	22	6	22	25°
65(2-1/2")	225	22	6	22	12°
80(3")	225	22	6	22	10°

Allowable Movements

1. Axial Compression 2. Axial Elongation 3. Transverse Movement 4. Angular Deflection



Operation Condition



- Operating Pressure 16 kg/cm²
- Burst Pressure 50 kg/cm²
- Vacuum Rating 400 mm/Hg
- Temperature - 20°C ~ 100°C

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Hoi Luen Hardware Co. Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.



海聯五金有限公司
 Hoi Luen Hardware Co., Ltd

Tel: (+852) 23887282
 E: Sales@hoiluenhardware.com W: www.hoiluenhardware.com